

# FITTING INSTRUCTIONS FOR CP0135BL/WH CRASH PROTECTORS HONDA CBR125

# <u>PLEASE NOTE THAT THE WAY THE KIT IS PACKED DOES NOT NECESSARILY REPRESENT THE WAY OF MOUNTING TO THE BIKE</u>

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – the rubber washers should be thrown away!

#### Nearside (left side as you sit on the bike)

- Remove lower fairing on both sides
- Remove two M8 bolts holding engine mount fixing
- Take one of the R&G aluminium blocks and fit to the frame, using two of the M8 cap head bolts supplied (fit M8 washer under head of each bolt)
- Note that the 10mm tapped hole goes towards the rear of the bike
- Tighten
- Place marking tool into 10mm thread in the block
- Replace fairing
- Push fairing against marking tool, until it makes a small impression on the inside of the fairing
- Remove fairing
- Drill pilot hole from inside to outside, picking up on the impression made by marking tool (suggest usng a 3mm drill bit)
- With marking tool still in the block, offer fairing back up to bike to check alignment
- Remove fairing and drill 28mm hole (recommended, but slightly larger is possible) from outside towards inside.
- Clean up the edges of the hole
- Remove marking tool and refit fairing
- Put M10 washer on one of the M10 bolts and pass through one of the crash protectors
- Place another M10 washer onto the open end of this assembly
- Pass assembly through fairing hole and into R&G aluminium block
- Tighten bolt until you feel some compression from inside the protector. Turn a little more so that you feel the
  compression increase slightly. Then apply a quarter turn. Do not overtighten as damage can occur to the
  bike. Do not exceed 40nm of torque.
- Note, complete this side before beginning right hand side, to avoid engine movement

## Offside (right side as you sit on the bike)

Repeat as per nearside, except using the spacer supplied, instead of the washer behind the crash protector assembly

Due to risk of cross-threading bolts etc; we recommend that our products be fitted by our official dealers or a qualified mechanic



### **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes.

Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products.

On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect.

Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned.

These terms do not affect the Buyer's statutory rights.

### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected)

Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor.

Goods must be in re-sellable condition, in the opinion of R&G Racing.

All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase).

The customer must pay any and all carriage charges.

No returns of discontinued products, unless within 14 days of purchase.

This policy does not affect your statutory rights and does not refer to faulty goods.